


Concentric Reducer M7150 & M7150F



Munro ductile iron grooved fittings are made to USA standards for consistent interchangeability with other major manufacturers. Pressure ratings conform to the pressure rating of installed couplings.



Materials

Ductile iron, non-lead orange rust-inhibiting paint coating, ASTM A536, Grade 65-45-12



Nominal Size	Pipe OD	Description	Dimensions	Approx. Weight	Model Number
			E-E		
in/mm	in/mm		in/mm	lb/kg	
2 X 1 50 X 25	2.37 X 1.31 60 X 33	Groove X Female NPT	2.5 63.5	1 0.45	M7150FX2X1
2 X 1 1/2 50 X 40	2.37 X 1.90 60 X 48		2.5 63.5	1 0.45	M7150FX2X150
4 X 2 100 X 50	4.50 X 2.37 114 X 60		3 76	2 0.9	M7150FX4X2
6 X 4 150 X 100	6.62 X 4.50 168 X 114		4 102	6 2.72	M7150FX6X4
10 X 8 250 X 200	10.75 X 8.62 273 X 219		6 152	14 6.35	M7150X10X8
12 X 10 300 X 250	12.75 X 10.75 323 X 273	Groove X Groove	7 178	28 12.7	M7150X12X10
6 X 2 150 X 50	6.62 X 2.37 168 X 60		4 102	5 1.8	M7150X6X2
6 X 4 150 X 100	6.62 X 4.50 168 X 114		4 102	5 2.26	M7150X6X4
8 X 4 200 X 100	8.62 X 4.50 219 X 114		5 127	11 5	M7150X8X4
8 X 6 200 X 150	8.62 X 6.62 219 X 168		5 127	9 4	M7150X8X6