SIMPLICITY PUMP STATIONS










DESIGNED
BUILT
TESTED
SERVICED


With a personal commitment to performance, reliability and ease of use.







Dimensions



Simplicity Pump Stations

This self-contained UL-QCZJ pumping station is a low-maintenance, high-value solution for commercial, agricultural, and residential irrigation systems.

- Suction lift or pressure boost Specify your application to get the configuration you need.
- True soft start and stop Can be started via pressure or clock.
- Constant pressure Avoid pressure changes on low-gallon zones.
- Quick ship Can ship in 4 weeks or less.
- Start-up and support Phone support from the Munro team as well as our national network of service providers.

The Simplest Professional-Grade Pump Station

- **Simple specifying** One part number, one product. It doesn't get any easier than that.
- Simple controls No throttling valves or dampeners means fewer controls for simpler operation.
- Simple maintenance Lower operating speeds means longer life for bearings and motors, while a soft-start and controlled ramp-up reduces water hammering.

Specifications

	НР	Incoming Power	Voltage	Starting Method	Discharge in	Suction in	Control	Suction Lift/ Pressure Boost	Approx Ship Weight Ibs	Model Number
		1PH	230	PRESSURE/ CLOCK	3	3	VFD	Suction Lift	320	SIMP23051PHSL
		3PH	230						320	SIMP23053PHSL
	_	3PH	460						320	SIMP46053PHSL
	5	1PH	230					Pressure Boost	336	SIMP23051PHBP
		3PH	230						336	SIMP23053PHBP
		3PH	460						336	SIMP46053PHBP

НР	Incoming Power	Voltage	Starting Method	Discharge in	Suction in	Control	Suction Lift/ Pressure Boost	Approx Ship Weight Ibs	Model Number
	1PH	230						330	SIMP23031PHBP
3	3PH	230	PRESSURE/ CLOCK	3	3	VFD	Pressure Boost	330	SIMP23033PHBP
	3PH	460	323010					330	SIMP46033PHBP

Munro's		
Simplicity Pump Stations vs. Competing Systems	Munro Simplicity	Other manufacturers
Variable Frequency Drive	✓ With built-in PLC	✓
Standard Marine Grade Aluminum Enclosure	✓	·
External Disconnect	~	~
Standard Run-Dry Protection	~	~
480V Model	✓	~
Intake and Discharge Isolation Valves	✓	Discharge Only
UL QCZJ Listed	~	Some Manufacturers
Bypass Piping	Standard on Boost Models	Add-on Option
Check Valve	Both Suction and Boost Models	Add-on Option
Warranty	2-5 year	1-2 year
Free Phone Tech Support	✓	35 Ajil (20)
Powder-Coated Steel Piping, Inside and Out	✓	一個 1
Self-Priming Pump for Suction Lift Applications	✓	

Features

■ VARIABLE FREQUENCY DRIVE WITH SMART SOFTWARE

Cost saving and environmentally conscience constant pressure flow control, with pump protection features: pressure surges, loss of prime, rapid cycling, dead heading, over pressure, motor overload, low/high voltage, protections.

- ENCLOSURE Powder-coated marine-grade aluminum offers durable, non-corrosive housing to stand up to the elements.
- PUMP Durable and long lasting centrifugal pumps for boost or suction lift applications, with superior performance to horsepower. Offered in 3hp and 5hp with top-of-the-line components that are only available as costly upgrades on other pumps.
- FITTINGS AND ACCESSORIES
 - From our rugged pipe and grooved couplings to the long-lasting gauges, valves and electrical components included, the Simplicity pump stations are complete with everything you need.
- SELF COOLING Vented for air flow to keep the pump cool.
- **SECURITY** Lockable enclosure.

Munro's packaged pump systems are designed to provide superior performance and value. These custom-engineered, integrated systems solve the problems associated with most small package systems by minimizing cost and complexity.

- 1.800.942.4270
- orders@munropump.com
- www.munropump.com

